



| 版次<br>(Version) | 变更内容<br>(Rev. Content) | 变更者<br>(Change Person) |
|-----------------|------------------------|------------------------|
|                 |                        |                        |
|                 |                        |                        |



| 技术参数 (Technical Data)       |                                         |         |         |         |
|-----------------------------|-----------------------------------------|---------|---------|---------|
| UL                          | 应用组别(Use group)                         | B       | C       | D       |
|                             | 额定电器参数<br>(Rated Electrical Parameters) | 300V/8A | 300V/8A | 300V/8A |
| IEC                         | 过压类别(Overvoltage Category)              | III/3   | III/2   | III/2   |
|                             | /污染等级(Pollution Degree)                 | 300V/8A | 300V/8A | 300V/8A |
| 压线范围(Wire Range)            |                                         |         |         |         |
| 工频耐压(Frequency Voltage)     |                                         |         |         |         |
| 冲击耐压(Rated Surge Voltage)   |                                         |         |         |         |
| 绝缘阻抗(Insulation Resistance) |                                         |         |         |         |
| 接触电阻(Contact Resistance)    |                                         |         |         |         |
| 剥线长度(String Length)         |                                         |         |         |         |
| 工作温度(Temperature)           |                                         |         |         |         |
| 额定扭矩(Rated torque)          |                                         |         |         |         |
| 材质和电镀(Material and plating) |                                         |         |         |         |
| 绝缘材质(Housing)               |                                         |         |         |         |
| 导体材料(Contact)               |                                         |         |         |         |
| /                           |                                         |         |         |         |

产品命名编码:  
(Product Number Code):

FPC1.5-XX-350-03-YY

系列(Series) — 型号(Model) — 极数(NO. of poles) — 塑体颜色(Housing Color) — 端子间距(Pitch)

|              |                         |
|--------------|-------------------------|
| 1:绿色(Green)  | 7:透明色<br>(Transparent)  |
| 2:蓝色(Blue)   | 8:白色(White)             |
| 3:黑色(Black)  | 9:黄色(Yellow)            |
| 4:灰色(Grey)   | Y:多种颜色<br>(Mixed color) |
| 5:橙色(Orange) |                         |
| 6:红色(Red)    |                         |

P=3.50mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p

| N | 02P   | 03P   | 04P   | 05P   | 06P   | 07P   | 08P   | 09P   | 10P   |
|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| L | 7.80  | 11.30 | 14.80 | 18.30 | 21.80 | 25.30 | 28.80 | 32.30 | 35.80 |
| B | 3.50  | 7.00  | 10.50 | 14.00 | 17.50 | 21.00 | 24.50 | 28.00 | 31.50 |
| N | 11P   | 12P   | 13P   | 14P   | 15P   | 16P   | 17P   | 18P   | 19P   |
| L | 39.30 | 42.80 | 46.30 | 49.80 | 53.30 | 56.80 | 60.30 | 63.80 | 67.30 |
| B | 35.00 | 38.50 | 42.00 | 45.50 | 49.00 | 52.50 | 56.00 | 59.50 | 63.00 |

|                                                                                                                                          |  |                       |                  |
|------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------|------------------|
|  东莞市澳斯电子有限公司<br>DONGGUAN AOSI ELECTRONICS CO., LTD. |  | 公差范围(Tolerance Range) |                  |
|                                                                                                                                          |  | 150~                  | ±1.50            |
| 型号(Type): FPC1.5-XX-350-03-YY                                                                                                            |  | 60~150                | ±1.00            |
| 核准(Approval):                                                                                                                            |  | 30~60                 | ±0.60            |
| 图号(Drawing NO.):                                                                                                                         |  | 6~30                  | ±0.40            |
| 核审(Audit):                                                                                                                               |  | 0~6                   | ±0.25            |
| 单位(Units):mm                                                                                                                             |  | 角度<br>(Angle)         | X ±2°<br>X.X ±1° |
| 设计(Design)                                                                                                                               |  | 比例(Scale):FULL        | 版次(Versio):T0    |