

Technical drawing of a multi-hole metal plate. The top view shows a plate with four rectangular holes and a central dashed line indicating a break. The overall width is labeled $(N \cdot 7.62) - 2$. The side view shows a cross-section of the plate with a thickness of 12.6 ± 0.2 . The distance from the top surface to the center of the holes is 26 ± 0.2 . The distance from the bottom surface to the center of the holes is 8.3 . The distance between the centers of the holes is 6.3 ± 0.15 . The bottom view shows a plate with four circular holes and a central dashed line indicating a break. The overall width is labeled $(N - 1) \cdot 7.62$. The distance from the left edge to the center of the first hole is 2.81 . The distance between the centers of the holes is 7.62 .

产品命名编码:
(Product Number Code):

系列 (Series)	型号 (Model)
极数 (N.O. of poles)	塑体颜色 (Housing Color)

1:绿色(Green)	7:透明色
2:蓝色(Blue)	(Transparent)
3:黑色(Black)	8:白色(White)
4:灰色(Grey)	9:黄色(Yellow)
5:橙色(Orange)	Y:多种颜色
6:红色(Red)	(Mixed color)

P=7.62mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	13.24	20.86	28.48	36.10	43.72	51.34	58.96	66.58	74.20
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	81.82	89.44	97.06	104.68	112.30	119.92	127.54	135.16	142.78
B	76.20	83.82	91.44	99.06	106.68	114.30	121.92	129.54	137.16

 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD.			公差范围(Tolerance Range)		
			150~	±1.50	
型号(Type): FPC2.5-XX-762-05-YY			60~150	±1.00	
			30~60	±0.60	
核准(Approval):			6~30	±0.40	
			0~6	±0.25	
核审(Audit):		单位(Units):mm	页码(Page):1/1	角度 X	±2°
				(Angle) X.X	±1°
设计(Design)		比例(Scale):FULL			版次(Version):T0