




P=5.08mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	2*2P	2*3P	2*4P	2*5P	2*6P	2*7P	2*8P	2*9P	2*10P
L	14.70	19.78	24.86	29.94	35.02	40.10	45.18	50.26	55.34
B	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72
N	2*11P	2*12P	2*13P	2*14P	2*15P	2*16P	2*17P	2*18P	2*19P
L	60.42	65.50	70.58	75.66	80.74	85.82	90.90	95.98	101.06
B	50.80	55.88	60.96	66.04	71.12	76.20	81.28	86.36	91.44

版次 (Vension)	变更内容 (Rev. Content)	变更者 (Change Person)


技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
	额定电器参数 (Rated Electrical Parameters)	300V/15A	300V/15A	300V/15A
IEC	过压类别(Overvoltage Category)	III/3	III/2	III/2
	/污染等级(Pollution Degree)			
	额定电器参数 (Rated Electrical Parameters)	300V/15A	300V/15A	300V/15A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 2500V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗(Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		≤8mΩ		
剥线长度(String Length)		/		
工作温度(Temperature)		-40° C--+105° C		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plsted)		
/		/		

产品命名编码:
(Product Number Code):

FPH2.5-XX-508-17R-YY

系列(Series) 型号(Model)
极数(NO. of poles) 塑体颜色(Housing Color)

端子间距(Pitch)	1:绿色(Green) 2:蓝色(Blue) 3:黑色(Black) 4:灰色(Grey) 5:橙色(Orange) 6:红色(Red)	7:透明色 (Transparent) 8:白色(White) 9:黄色(Yellow) Y:多种颜色 (Mixed color)
-------------	---	--

 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD,		公差范围(Tolerance Range)	
		150~	±1.50
型号(Type): FPH2.5-XX-508-17R-YY		60~150	±1.00
		30~60	±0.60
核准(Approval): 图号(Drawing NO.):		6~30	±0.40
		0~6	±0.25
核审(Audit): 单位(Units):mm 页码(Page):1/1		角度 (Angle)	X ±2° X.X ±1°
		设计(Design)	比例(Scale):FULL  版次(Versio):T0