

										版次 (Vension)	变更内容 (Rev. Content)	变更者 (Change Person)
										技术参数 (Technical Data)		
UL	应用组别(Use group)		B	C	D							
	额定电器参数 (Rated Electrical Parameters)		300V/15A	300V/15A	300V/15A							
IEC	过压类别(Overvoltage Category) /污染等级(Pollution Degree)		III/3	III/2	III/2							
	额定电器参数 (Rated Electrical Parameters)		300V/15A	300V/15A	300V/15A							
压线范围(Wire Range)			/									
工频耐压(Frequency Voltage)			AC 1600V									
冲击耐压(Rated Surge Voltage)			4000V									
绝缘阻抗(Insulation Resistance)			DC500V 500MΩ above									
接触电阻(Contact Resistance)			≤20mΩ									
剥线长度(String Length)			/									
工作温度(Temperature)			-40° C--+105° C									
额定扭矩(Rated torque)			/									
材质和电镀(Material and plating)												
绝缘材质(Housing)			PA66									
导体材料(Contact)			铜合金, 镀锡(Copper alloy, Sn plsted)									
/			/									

产品命名编码:
(Product Number Gode):

FPM2.5-XX-508-13-YY

系列(Series)

极数(NO. of poles)

端子间距(Pitch)

型号(Model)

塑体颜色(Housing Color)

1:绿色(Green)

2:蓝色(Blue)

3:黑色(Black)

4:灰色(Grey)

5:橙色(Orange)

6:红色(Red)

7:透明色
(Transparent)

8:白色(White)

9:黄色(Yellow)

Y:多种颜色
(Mixed color)

P=5.08mm,N为孔位数(N for hole digits),有效位数为 (Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	12.16	17.24	22.32	27.40	32.48	37.56	42.64	47.72	52.80
B	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	57.88	62.96	68.04	73.12	78.20	83.28	88.36	93.44	98.52
B	50.80	55.88	60.96	66.04	71.12	76.20	81.28	86.36	91.44

 东莞市奥斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD,		公差范围(Tolerance Range)	
型号(Type): FPM2.5-XX-508-13-YY		150~	±1.50
核准(Approval):		60~150	±1.00
图号(Drawing NO.):		30~60	±0.60
核审(Audit):		6~30	±0.40
单位(Units):mm		0~6	±0.25
比例(Scale):FULL		角度 X	±2°
设计(Design)		(Angle) X.X	±1°
		版次(Version):T0	