



产品命名编码:
(Product Number Code):

系列 (Series)

极数 (NO. of poles)

端子间距(Pitch)

型号(Model)

塑体颜色(Housing Color)

- | | |
|--------------|---------------|
| 1:绿色(Green) | 7:透明色 |
| 2:蓝色(Blue) | (Transparent) |
| 3:黑色(Black) | 8:白色(White) |
| 4:灰色(Grey) | 9:黄色(Yellow) |
| 5:橙色(Orange) | Y:多种颜色 |
| 6:红色(Red) | (Mixed color) |

P=7.62mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p

N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	13.24	20.86	28.48	36.10	43.72	51.34	58.96	66.58	74.20
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	81.82	89.44	97.06	104.68	112.30	119.92	127.54	135.16	142.78
B	76.20	83.82	91.44	99.06	106.68	114.30	121.92	129.54	137.16

 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD.			公差范围(Tolerance Range)		
			150~	±1.50	
型号(Type): FPM2.5-XX-762-00R-YY			60~150	±1.00	
			30~60	±0.60	
核准(Approval):			6~30	±0.40	
			0~6	±0.25	
图号(Drawing NO.):			角度	X	
				±2°	
核审(Audit):		单位(Units):mm	页码(Page):1/1	(Angle)	X.X
					±1°
设计(Design)		比例(Scale):FULL			版次(Version):T0