

版次 (Vension)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
	额定电器参数 (Rated Electrical Parameters)	300V/15A	300V/15A	300V/15A
IEC	过压类别(Overvoltage Category) /污染等级(Pollution Degree)	III/3	III/2	III/2
	额定电器参数 (Rated Electrical Parameters)	300V/15A	300V/15A	300V/15A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 2500V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗(Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		≤20mΩ		
剥线长度(String Length)		10		
工作温度(Temperature)		-40° C--+105° C		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plsted)		
/		/		

产品命名编码:
(Product Number Code):

FPM4-XX-762-00-YY

系列 (Series)


极数 (NO. of poles)

端子间距 (Pitch)

型号 (Model)

塑体颜色 (Housing Color)

- | | |
|---------------|----------------------|
| 1:绿色 (Green) | 7:透明色 (Transparent) |
| 2:蓝色 (Blue) | 8:白色 (White) |
| 3:黑色 (Black) | 9:黄色 (Yellow) |
| 4:灰色 (Grey) | Y:多种颜色 (Mixed color) |
| 5:橙色 (Orange) | |
| 6:红色 (Red) | |



P=7.62mm,N为孔位数(N for hole digits),有效位数为 (Significant Digits):02p-19p

	N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L		13.24	20.86	28.48	36.10	43.72	51.34	58.96	66.58	74.20
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58
	N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L		81.82	89.44	97.06	104.68	112.30	119.92	127.54	135.16	142.78
B		76.20	83.82	91.44	99.06	106.68	114.30	121.92	129.54	137.16

东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD,		公差范围 (Tolerance Range)	
		150~	±1.50
型号 (Type): FPM4-XX-762-00-YY		60~150	±1.00
核准 (Approval):		图号 (Drawing NO.):	30~60 ±0.60
核审 (Audit):		单位 (Units): mm	6~30 ±0.40
设计 (Design)		页码 (Page): 1/1	0~6 ±0.25
		角度 (Angle)	X ±2°
		X.X	±1°
		版次 (Version): T0	