

版次 (Vension)		变更内容 (Rev. Content)		变更者 (Change Person)	

技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
	额定电器参数 (Rated Electrical Parameters)	300V/30A	300V/30A	300V/30A
IEC	过压类别(Overvoltage Category) /污染等级(Pollution Degree)	III/3	III/2	III/2
	额定电器参数 (Rated Electrical Parameters)	300V/30A	300V/30A	300V/30A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 2500V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗(Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		≤20mΩ		
剥线长度(String Length)		10		
工作温度(Temperature)		-40° C--+105° C		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plsted)		
/		/		

7.62(XX+1)

7.62(XX+2)

14.25

29.00

7.62

5.00

产品命名编码:
(Product Number Code):

FPM4-XX-762-04R-YY

系列(Series)

极数(NO. of poles)

端子间距(Pitch)

型号(Model)

塑体颜色(Housing Color)

1:绿色(Green)
2:蓝色(Blue)
3:黑色(Black)
4:灰色(Grey)
5:橙色(Orange)
6:红色(Red)
7:透明色
(Transparent)
8:白色(White)
9:黄色(Yellow)
Y:多种颜色
(Mixed color)

P=7.62mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02
B	76.20	83.82	91.44	99.06	106.68	114.30	121.92	129.54	137.16

AOSI 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO.,LTD,		公差范围(Tolerance Range)	
型号(Type): FPM4-XX-762-04R-YY		150~	±1.50
		60~150	±1.00
核准(Approval): 图号(Drawing NO.):		30~60	±0.60
		6~30	±0.40
核审(Audit): 单位(Units):mm 页码(Page):1/1		0~6	±0.25
		角度 X (Angle) X.X	±2° ±1°
设计(Design) 比例(Scale):FULL		版次(Version):T0	