





版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
IEC	额定电器参数 (Rated Electrical Parameters)	300V/8A	300V/8A	300V/8A
	过压类别(Overvoltage Category) /污染等级(Pollution Degree)	III/3	III/2	III/2
	额定电器参数 (Rated Electrical Parameters)	300V/8A	300V/8A	300V/8A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 1300V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗(Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		≤20mΩ		
剥线长度(String Length)		/		
工作温度(Temperature)		-40° C--+105° C		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plsted)		
/		/		

产品命名编码:
(Product Number Code):

FPS1.5-XX-381-02-YY

系列(Series) — 型号(Model)
极数(NO. of poles) — 塑体颜色(Housing Color)

端子间距(Pitch)

- 1:绿色(Green)
- 2:蓝色(Blue)
- 3:黑色(Black)
- 4:灰色(Grey)
- 5:橙色(Orange)
- 6:红色(Red)
- 7:透明色
(Transparent)
- 8:白色(White)
- 9:黄色(Yellow)
- Y:多种颜色
(Mixed color)

P=3.81mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	8.11	11.92	15.73	19.54	23.35	27.16	30.97	34.78	38.59
B	3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	42.40	46.21	50.02	53.83	57.64	61.45	65.26	69.07	72.88
B	38.10	41.91	45.72	49.53	53.34	57.15	60.96	64.77	68.58

 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD.		公差范围(Tolerance Range)	
		150~	±1.50
		60~150	±1.00
型号(Type): FPS1.5-XX-381-02-YY		30~60	±0.60
核准(Approval):		6~30	±0.40
图号(Drawing NO.):		0~6	±0.25
核审(Audit):		角度 (Angle)	X ±2° X.X ±1°
单位(Units):mm		页码(Page):1/1	
设计(Design)		比例(Scale):FULL	版次(Version):T0