

										版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)
										技术参数 (Technical Data)		
UL	应用组别(Use group)		B	C	D							
	额定电器参数 (Rated Electrical Parameters)		160V/8A	160V/8A	320V/8A							
IEC	过压类别 (Overvoltage Category)		III/3	III/2	III/2							
	/污染等级 (Pollution Degree)											
额定电器参数 (Rated Electrical Parameters)		160V/8A	160V/8A	320V/8A								
压线范围(Wire Range)			/									
工频耐压(Frequency Voltage)			AC 2500V									
冲击耐压(Rated Surge Voltage)			4000V									
绝缘阻抗(Insulation Resistance)			DC500V 500MΩ above									
接触电阻(Contact Resistance)			≤20mΩ									
剥线长度(String Length)			/									
工作温度(Temperature)			-40° C--+105° C									
额定扭矩(Rated torque)			/									
材质和电镀(Material and plating)												
绝缘材质(Housing)			PA66									
导体材料(Contact)			铜合金, 镀锡(Copper alloy, Sn plisted)									
/			/									

产品命名编码:
(Product Number Code):

FS1.5-XX-700-04-YY

系列(Series)

极数(NO. of poles)

端子间距(Pitch)

型号(Model)

塑体颜色(Housing Color)

1:绿色(Green)

2:蓝色(Blue)

3:黑色(Black)

4:灰色(Grey)

5:橙色(Orange)

6:红色(Red)

7:透明色
(Transparent)

8:白色(White)

9:黄色(Yellow)

Y:多种颜色
(Mixed color)

P=7.00mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	12.20	19.20	26.20	33.20	40.20	47.20	54.20	61.20	68.20
B	7.00	14.00	21.00	28.00	35.00	42.00	49.00	56.00	63.00
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	75.20	82.20	89.20	96.20	103.20	110.20	117.20	124.20	131.20
B	70.00	77.00	84.00	91.00	98.00	105.00	112.00	119.00	126.00

AOSI 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO.,LTD,			公差范围(Tolerance Range)	
型号(Type): FS1.5-XX-700-04-YY			150~	±1.50
			60~150	±1.00
核准(Approval):图号(Drawing NO.):			30~60	±0.60
			6~30	±0.40
核审(Audit):单位(Units):mm页码(Page):1/1			0~6	±0.25
			角度 (Angle)	X X.X
设计(Design)比例(Scale):FULL			版次(Version):T0	