




版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
	额定电器参数 (Rated Electrical Parameters)	300V/15A	300V/15A	300V/15A
IEC	过压类别(Overvoltage Category) /污染等级(Pollution Degree)	III/3	III/2	III/2
	额定电器参数 (Rated Electrical Parameters)	300V/15A	300V/15A	300V/15A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 2500V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗(Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		≤20mΩ		
剥线长度(String Length)		/		
工作温度(Temperature)		-40° C--+105° C		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plsted)		
/		/		

产品命名编码:
(Product Number Code):

系列(Series) — 型号(Model) — 极数(NO. of poles) — 端子间距(Pitch) — 塑体颜色(Housing Color)

FPC2.5-XX-750-22-YY

1:绿色(Green) 7:透明色
2:蓝色(Blue) (Transparent)
3:黑色(Black) 8:白色(White)
4:灰色(Grey) 9:黄色(Yellow)
5:橙色(Orange) Y:多种颜色
6:红色(Red) (Mixed color)

P=7.50mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	14.00	21.50	29.00	36.50	44.00	51.50	59.00	66.50	74.00
B	7.50	15.00	22.50	30.00	37.50	45.00	52.50	60.00	67.50
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	81.50	89.00	96.50	104.00	111.50	119.00	126.50	134.00	141.50
B	75.00	82.50	90.00	97.50	105.00	112.50	120.00	127.50	135.00

 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD,		公差范围(Tolerance Range)	
		150~	±1.50
型号(Type): FPC2.5-XX-750-22-YY		60~150	±1.00
核准(Approval): 图号(Drawing NO.):		30~60	±0.60
核审(Audit): 单位(Units):mm 页码(Page):1/1		6~30	±0.40
设计(Design): 比例(Scale):FULL		0~6	±0.25
		角度(Angle)	X ±2° X.X ±1°
		版次(Version):T0	