


版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
	额定电器参数 (Rated Electrical Parameters)	150V/4A	150V/4A	150V/4A
IEC	过压类别 (Overvoltage Category) / 污染等级 (Pollution Degree)	III/3	III/2	III/2
	额定电器参数 (Rated Electrical Parameters)	150V/4A	150V/4A	150V/4A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 1300V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗 (Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		≤20mΩ		
剥线长度(String Length)		/		
工作温度(Temperature)		-40° C--+105° C		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plsted)		
/		/		

产品命名编码:
(Product Number Code):

FPM1.5-XX-250-24-YY

系列(Series) — 型号(Model) — 塑体颜色(Housing Color)

极数(NO. of poles) — 端子间距(Pitch)

1:绿色(Green)	7:透明色 (Transparent)
2:蓝色(Blue)	8:白色(White)
3:黑色(Black)	9:黄色(Yellow)
4:灰色(Grey)	Y: 多种颜色 (Mixed color)
5:橙色(Orange)	
6:红色(Red)	

P=2.50mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p									
N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	8.40	10.90	13.40	15.90	18.40	20.90	23.40	25.90	28.40
B	2.50	5.00	7.50	10.00	12.50	15.00	17.50	20.00	22.50
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	30.90	33.40	35.90	38.40	40.90	43.40	45.90	48.40	50.90
B	25.00	27.50	30.00	32.50	35.00	37.50	40.00	42.50	45.00

东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD.			公差范围(Tolerance Range)	
型号(Type): FPM1.5-XX-250-24-YY			150~	±1.50
核准(Approval):			60~150	±1.00
图号(Drawing NO.):			30~60	±0.60
核审(Audit):			6~30	±0.40
单位(Units):mm			0~6	±0.25
页码(Page):1/1			角度 (Angle)	X ±2° X.X ±1°
设计(Design)			比例(Scale):FULL	版次(Version):T0